

PENTAX

Positioning Systems

Precision Satellite Surveying

**Model
G7H**

GPS | GLONASS | BEIDOU | SBAS | GALILEO



- + Compact and durable metal housing
- + Better dust and weather resistance (IP67)
- + Equipped with IMU sensor that compensates tilting of the receiver
- + WiFi for direct communication with web browser for e.g. downloading data, firmware upgrades and communication between receiver and controller

TI Asahi Co.,Ltd
Focusing on true performance

GNSS SPECIFICATIONS

Model

G7H

Channel Configuration		800 channels
		Multi-Frequency GPS, GLONASS Beidou, Galileo, QZSS and Atlas
Receiver Board		P20
Signal Tracking	GPS	L1 C/A, L1P, L1C, L2P, L2C, L5
	GLONASS	G1, G2, G3, P1, P2
	BEIDOU	B1i, B2i, B3i, B10C, B2A, B2B, ACEBOC
	Galileo	E1BC, E5a, E5b, E6BC, ALTBOC
	QZSS	L1 C/A, L1C, L2C, L5, LEX
	SBAS	L1 C/A, L5
	NavIC (IRNSS) *1	L5
	L-Band	Atlas
Position Accuracy	SBAS (WAAS, GAGAN etc.)	0.3 m
	DGPS	0.4 m
RTK Performance	Horizontal Accuracy (Single baseline)	8 mm + 1 ppm
	Vertical Accuracy (Single baseline)	15 mm + 1 ppm
	Horizontal Accuracy (Network RTK)	8 mm + 0.5 ppm
	Vertical Accuracy (Network RTK)	15 mm + 0.5 ppm
	Average Time to Work	Typ. < 10 sec.
	Availability/Initialization Reliability	> 99.9%
Static Performance	Horizontal Accuracy(Long time observation) *2	3 mm + 0.1 ppm
	Vertical Accuracy(Long time observation) *2	3.5 mm + 0.4 ppm
	Horizontal Accuracy	3 mm + 0.5 ppm
	Vertical Accuracy	5 mm + 0.5 ppm
PPP (Precision Point Positioning)	With Atlas Basic (Optional)	0.50 m
	With Atlas H30 (Optional)	0.15 m
	With Atlas H10 (Optional)	0.04m
Ports		Lemo 5-pin, external radio and power supply Lemo 7-pin, serial port and USB
Internal Radio Modem	Frequency	410 Mhz - 470 Mhz
	Output Power	0.5 W / 1 W
GSM/GPRS Modem	Frequency Bands	LTE FDD / LTE TDD / WCDMA / CDMA / GSM
	Network Protocol	NTRIP, HTTP, FTP
Power	Internal Battery	3,350 mAh / 7.4 V x2
	Current Drain	0.35 A / 12 V
		1.25 A / 12 V max.
	Battery Running Time	Approx. 12 hr: Rover, 10 hr: Base with 2 Batteries
Weight		1.1 kg with 2 batteries
Dimensions		Ø 130 mm x H 100 mm
Environmental Specifications	Operating Temperature	-30 °C to +65 °C
	Storage Temperature	-30 °C to +65 °C
	Shock/Drop	2 m
Velocity Accuracy	Standalone	0.007 m/sec, 0.020 m/sec
Data Output	Raw Data	10 Hz (20 Hz optional)
	NMEA Data	10 Hz (20 Hz optional)
	Correction data	RTCM Ver 2.1, 2.2, 2.3, 3.0, 3.1, 3.2 CMR, CMR+, sCMRx
Time to First Fix	Cold Start	< 60 sec
	Warm Start	< 10 sec
	Re-acquisition	< 1 sec
WiFi		IEEE 802.11b/g
IMU		Calibration free with range 30°/< 30mm
Bluetooth		Class 2
Memory		Internal 8 GB and MicroSD 8 GB
RoHS		Complied
Waterproofing		IP67
Certification		CE
Standard Accessories		2 x Li-Ion rechargeable battery pack
		Battery charger + AC Adapter
		5/8 inch screw adapter
		Lemo 7-pin communication cable
		CD (contains manual and data conversion software)

*1 Hardware ready

*2 Performance, Accuracy and Reliability are dependent upon various factors including satellite geometry, number of satellites, ionospheric conditions, atmospheric conditions and multipath.

PENTAX Positioning System is dedicated to providing customers with first class positioning system products and freedom of choice. We have carefully designed high-quality products to meet the needs of today's surveyors based on the experience of many years involved in instrument design and construction. Our engineers have been involved in Survey products since the beginning of the Satellite Surveying Era. We are committed to ease of use, a low cost of ownership and flexibility to accommodate different working environments. Our close partners are carefully chosen and are committed to these values as we are.

TI Asahi Co., Ltd.

International Sales Department

4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi

Saitama, 339-0073 Japan

Tel.: +81-48-793-0118

Fax: +81-48-793-0128

E-mail: International@tiasahi.com

www.pentaxsurveying.com/en/

Your Official Pentax Dealer



The CE marking assures that this product complies with the requirements of the EC directive for safety.

JSIMA
Japan Surveying Instruments Manufacturers' Association

Member symbol of the Japan Surveying Instruments Manufacturers' Association representing the high quality surveying products.